

RIMAGE AUTOPRINTER TECHNICAL SPECIFICATIONS

Standard Systems	Rimage AutoEverest III, AutoEverest 600, AutoPrism <i>Plus!</i>
Software Requirements	Rimage CD Designer™ Software Suite or other graphics application
Input Capacity	Four-bin, rotating carousel holds up to 300 discs
Output Capacity	Four-bin, rotating carousel holds up to 300 discs
Physical Size	Height: 22.375 inches (56.8 cm) Width: 15.063 inches (38.4 cm) Depth: 22.625 inches (57.5 cm) (Leave an additional 3.5 inches (9 cm) for cables)
Weight	AutoEverest III and AutoEverest 600: 97 pounds (44.1 kg) AutoPrism <i>Plus!</i> : 73 pounds (33.2 kg)
Minimum PC Requirements	Processor: Pentium II, 450 MHz or higher RAM/memory: 256 MB One USB 1.0 port One Parallel port (AutoPrism <i>Plus!</i> only)
Minimum Macintosh Requirements	G4 256 MB One USB 1.0 port (AutoEverest III and AutoEverest 600)
Supported Operating Systems	Windows 2000 Professional with SP4, Windows XP Professional with SP1 or SP2, and Windows Server 2003 Macintosh OS X version 10.3 or version 10.4 (AutoEverest III and AutoEverest 600 only)
Power	100 to 240 VAC, 1.5 A, 50/60 Hz
Temperature Requirements	Operating Temperature: 60 to 80°F (16 to 27°C) Storage Temperature: 5 to 95°F (-15 to 35°C)
Humidity Requirements	40% to 80% non-condensing
Media Requirements	Rimage recommends Rimage Brand Media Kits for use in all AutoPrinters
Ribbon Requirements	Rimage recommends Rimage Brand Ribbons and Media Kits for use in all AutoPrinters
Label Design Requirements	Refer to your AutoPrinter User Guide for label design requirements

For additional specifications, refer to your printer user guide or www.rimage.com.